



Dimmable LED PAR38

Ordering Information

Model No.	Item name	Lumens ² (lm)	Watts (w)	CCT ¹ (k)	Efficacy (lm/w)	CRI	Lifetime ³ (h)	Beam Angle	Base type	Voltage (v)	Cerification	Equivalent ⁴ (w)
L4-PAR38D-15W	PAR38	1250	15	2700/3000/4000K	83	80	25000	40°	E26	120	UL, CUL, Energy Star	120

**3 THREE YEARS
WARRANTY**



1. CCT Range complies to ANSI C78.377-2008.

2. Thermally stable typical lumens (± 10%)

3. Rated life is based on 70% lumen maintenance, and engineering testing and probability analysis.

4. Equivalency based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.

5. Energy Star® are available.

Note: All Information consistent with IESNA LM-80-08 results and IESNA LM-79-08 testing completed by a qualified third party facility.

Note: All lamps meet Energy Star® Integral LED Lamp requirements, and has been submitted for testing.

Dimensions

Model	MOL	Diameter
PAR38	5.16"	4.72"



Note: Lamp shape conforms to ANSI C78.21-2003.

Note: Designed to comply with RoHS Directive 2002/95/EC.

Energy Savings

Model No.	Equivalent	Energy Savings
L4-PAR38D-15W	120W Incandescent	\$289

*Actual Equivalent Replacement, based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.

Note: Energy Savings based on using one bulb for 25,000 hr rated life at 11¢/kWh. Does not include maintenance and replacement lamp savings.