

## DOUBLE SIDED TUBE - 6000K

### Description:

Highly efficient double-sided tube uses SMD2835 technology for maximum lumen output. This energy saving tube, with its high lumen output, is suitable for use in commercial applications.

### Features:

- Can be powered from RDC end cap or Bi-Pin end cap.
- Direct fit florescent fixtures without the need of a ballast.
- High bright chip SMD to save more energy and increase life time.



### Applications:

- Box sign
- Signage

### Accessories:

- Clips Included





### Technical Specification:

<b>Length</b>	7ft	8ft
<b>Wattage</b>	36W	40W
<b>Input Voltage</b>	100-277V AC	100-277V AC
<b>Color Temperature</b>	6000K	6000K
<b>Lumen Output</b>	4680 LM	5200 LM
<b>Lens Type</b>	Clear	Clear
<b>Beam Angle</b>	360°	360°
<b>CRI</b>	80	80
<b>IP Rating</b>	IP20	IP20
<b>Warranty</b>	5 Years	5 Years

<b>Ordering Guide</b>		Example: T8-D-7FT-36W-6000K-CLR		
Fixture Type <b>T8-D</b>	Length <input type="text"/>	Wattage <input type="text"/>	Color Temperature <input type="text"/>	Lens Type <b>CLR</b>
(Double sided tube)	<b>7FT</b> <b>8FT</b>	<b>36W</b> <b>40W</b>	<b>6000K</b>	<b>CLR (Clear)</b>